4 Panel Mirror
For all Club Car DS 2000.5-Present
MRR CC2 4PNLK

⚠ **CAUTION:** Remember to wear appropriate eye protection while performing the tasks in this instruction.

Hardware Included:
A) 100B brackets (2) for 2000.5-Present Club Car DS
B) Bracket mounting screws (4)
C) Flat head bolt (1)
D) Knobs (2)
E) Nuts (2) and Lock Washers (2)

Installation Instructions:

1. Before proceeding, check that all parts listed above are in the parts bag.
2. Assemble the parts to both ends of the Panel Mirror as shown in Figure 1. Place lock washer inside of knob. Place nut on top of lock washer inside of knob. Place mounting bracket over the bolt, and attach knob.
3. Hand tighten knobs at this time.
4. Locate mounting points for the mirror. (See Figure 2)
5. Hold the assembled mirror up to the selected mounting point.
6. Install the assembly below the metal front strut curvature. Once in place, mark a top hole in bracket with marker (either side), and drill the top hole with a 1/8" drill bit. Set the mirror assembly in place and install one screw at this time. Rotate the assembly in place making sure it is level and drill/install the other top screw. Tighten the top two screws securely and drill the bottom holes at this time and install the screws. You can now adjust the mirror to desired level.
7. To readjust the mirror for other drivers, simply loosen the knobs slightly on either end of the mirror and retighten after adjustment has been made. DO NOT OVER TIGHTEN to avoid stripping threads or breaking a knob.
8. To clean mirror glasses, use any proprietary window cleaner and non abrasive, cotton cloth. DO NOT USE any abrasive type of cleaner such as those used on car body or kitchen appliances or utensils.

NOTE: All other brackets included are for other applications and will not be used for this particular application.

Figure 1

Figure 2

C 907