

# RS CC2W WHT BLK & RS CC2W BGE BLK REAR SEAT Installation Instructions for Club Car 2000-2003



**BUGGIES**  
UNLIMITED



**NOTE: Do not tighten any bolts until installation is complete. All bolts include washers for the Hex Head side and the threaded side. Please use both!!**

- 1) Remove bumper, backrest, cushions, and backrest supports.
- 2) Replace backrest supports with **(a)** using bolts that you removed from factory back rest.
- 3) Mount cross member support arms made from  $\frac{3}{4}$ " Square Tubing **(b)** to the outside of the seatback supports using  $\frac{5}{16}$  X 2" bolts.
- 4) Attach "U" bracket **(c)** to the other end of support arms using  $\frac{5}{16}$  X 2  $\frac{1}{2}$ " bolts.
- 5) Attach support arms **(d)** to inside of seat mainframe **(e)** using 2 -  $\frac{5}{16}$  X 2  $\frac{1}{2}$ " bolts. Do this on each side of the seat.
- 6) Mount the step **(f)** with  $\frac{1}{4}$  X 3  $\frac{1}{2}$ " hardened bolts and washers, through the bottom of the "U" bracket, then through the existing holes in the car, and then through the holes in the step.
- 7) Mount mainframe **(e)** on the cross arms **(b)** using 4 -  $\frac{1}{4}$  X 1  $\frac{3}{4}$ " hardened bolts. Then mount bars **(d)** through the slots into the outside of step **(f)** using 2 -  $\frac{5}{16}$  X 2  $\frac{1}{2}$ " bolts.
- 8) At this time tighten down all bolts.



Buggies Unlimited  
1-888-444-9994  
[www.buggiesunlimited.com](http://www.buggiesunlimited.com)