

BU8500BEZ GOLF CART CLUB COVER

Installation and Folding Instructions for EZGO TXT Models

1. Center the awning track on the inside rear of the roof and install five sheet metal screws.

DRILLING IS NOT REQUIRED. SCREWS ARE SELF-TAPPING.




2. Center the cross bar between the two vertical roof support posts on the forward side of the posts. (You will have to detach the cross bar from each end and reinstall it in front of the roof support posts.)



3. Install the plastic clips on the cross bar and align with the roof support posts so that the flat side of the clip rests against the support post.


Option 1

Wrap two plastic ties diagonally around each intersection where the cross bar meets the roof support posts and pull tight. Cut the excess off the plastic ties.



Option 2

Drill a 1/8" hole through the cross bar, plastic clip, and into the roof support post. DO NOT DRILL THROUGH BOTH SIDES OF THE ROOF SUPPORTS. Install a 1-1/2" sheet metal screw in the hole. DO NOT USE AN ELECTRIC SCREWDRIVER.



Folding Instructions

1



Lay the valance up and onto the roof.

2



Fold the center rear clear vinyl section over and on the top of the canopy. Fold both sides of the clear vinyl panels forward as shown.

3



Detach the velcro straps on the underside of both panels. Fold both side panels including the clear vinyl panels up on top of the canopy.

4



Fold the rear frame of the canopy forward to rest against the cart roof

5



Fold the hanging canopy shell up (in half) exposing the velcro strip. Pull the valance down from the roof and match with the velcro on the awning.

Buggies Unlimited
1-888-444-9994
www.buggiesunlimited.com