

Roof Rack Cargo Box

EZGO Medalist/TXT 1994-Present

TOP EZ9 RACK



BUGGIES
UNLIMITED

CONTENTS:

- (1) Roof Rack Cargo Box
- (4) 10mm Screws
- (4) Nuts
- (8) Washers
- (4) Rubber Spacers
- (4) Plastic Spacers

Tools Needed:

- 10 mm Ratchet
- 10 mm Open Faced Wrench

Installation Instructions:

1. Locate existing (4) 1/4" X 20 Phillips head screws mounting canopy to roof supports. Discard screws at this time.
2. Locate both sets of spacers in included hardware, and align with mounting holes on top of canopy. NOTE: Flat rubber spacer goes on the bottom. (See Figure 1)
3. Lift cargo box to top of canopy and align mounting brackets on rack with spacers. NOTE: Front canopy mounting holes are wider than rear.
4. Align washers on top of mounting rack brackets. Insert 10mm screws through washer, rack brackets, and spacers. NOTE: Be sure screw goes all the way through canopy and strut, and is accessible through bottom side of canopy.
5. Attach washer and nut to bottom side of screws. (See Figure 2)
6. Tighten all hardware at this time using 10mm ratchet and 10mm open faced wrench. (See Figure 3)



Figure 1



Figure 2




Figure 3

CAUTION: Carrying capacity of roof rack should not exceed 25 pounds.