

HARDWARE LIST

YAMAHA DRIVE 07-PRESENT

PART NUMBER

- 31773-Suite Seats Solid Black G29
- 31778-Suite Seats Black/Tan G29
- 31783-Suite Seats Solid Tan G29
- 31788-Suite Seats Black/Silver G29
- 31793-Suite Seats Black/White G29
- 31795-Suite Seats Special Order G29

(4) SEAT SPACERS
USE 2 PER SIDE

(4) 1/4x20 - 1" HEX HEADS
ALREADY INSERTED IN
HINGE TAB MOUNT HOLES



(4) 1/4x20 - 2.50" HEX HEADS
FOR MOUNTING
SEAT BACKS



(8) 1/4x20 - 2.25" HEX HEADS
FOR MOUNTING
HIP RESTRAINTS





Caution: Wear Appropriate Eye Protection!



FIGURE 1



FIGURE 2



FIGURE 3



FIGURE 4

INSTALLATION INSTRUCTIONS YAMAHA DRIVE SERIES 2007 + PART NUMBER

- 1.) Remove side handles and mounting hardware from stock seat base.
- 2.) Install handles on seat base using 2.25" hex head bolts. Install hinge tabs on seat base using 1" hex head bolts. ***IMPORTANT*** Hand start all bolts to prevent damage to t-nuts. Seat base can now be installed on cart.
- 3.) Remove stock seat back.
- 4.) Using the 2.50" hex head bolts provided, install seat backs. Start by placing 2 spacers on each side of seat back mount then sliding bolts through spacers and into seat backs. (Figure 3) Spacers should be placed to provide clearance for bolts that protrude from cart basket. ***IMPORTANT*** Start all bolts by hand to prevent damage to t-nuts.